



Specifications to Suit Your Needs, Imperial - 2016

Model, √ = Stanard, O = Option,	0.70	1.75	3.50 SD	3.50 WA	500 SD	6.75 SD	3.50 TD	6.75 TD	3.50 PTO	6.75 PTO	12.75 PTO	T1300 PTO	PT2600 PTO
UV & Corrosion Resistant Hopper & Guards	√	√	√	√	√	√	√	√	√	√	√	√	√
Robust Construction & Hot Dip Galvanised Frame	√	√	√	√	√	√	√	√	√	√	√	√	√
Stainless Steel Shutter	√	√	√	√	√	√	√	√	√	√	√	√	√
Full Magnesium Shroud	√	O											
Extra Bearing About Gearbox	√	√	√	√	√	√	√	√					
Dished Spinner & Tipped Vanes	√	√	√	√	√	√	√	√	√	√	√	√	√
Twin Spinner Disc's												√	√
Mudguards	O	O	√	√	√	√	O	O					
Adjustable Drawbar	√	√	√	√	√	√	√	√					
PVC Hopper Cover	O	√	√	√	√	√	√	√	√	√	√	√	√
Polyethylene Hopper Hard Lid	√	O	O	O	O	O	O	O	O	O	O		
Simple-Drive, Engage Gearbox from Quad Seat	√	√	√	√	√	√	√	√					
Pin Drive Gearbox Drive	O	O	O										
Hydraulic Open/Shut									O	O	√	√	√
Horticulture Accessories: Side Dresser Kit		O	O	O	O	O			O	O			
Flat Spinner & Vanes		O	O	O	O	O	O	O	O	O	O	O	O
Tyres: 18/750-8	√	√											
18/950-8 Nobby							√	√					
18/950-8			√										
20/10-8				√	√	O							
20/11-8 Flotation				O	O	√							
Working Bout Width @													
9 mph		40ft	40ft	40ft	40ft	40ft	40ft	40ft					
400 rpm at PTO									40ft	40ft	40ft		
540 rpm at PTO												12 - 65ft	13 - 65ft
Capacity:													
Cubic Feet	2.5	6	12.5	12.5	17.5	24	12.5	24	12.5	24	45	45	90
Mag Powder (55lb Bag)	2 x bag	6 x bags											
Urea	120lb	310lb	620lb	620lb	880lb	1100lb	620lb	1100lb	620lb	1100lb	2250lb	2250lb	4580lb
DAP	155lb	385lb	770lb	770lb	1100lb	1490lb	770lb	1490lb	770lb	1490lb	2810lb	2810lb	5720lb
Superphosphate		420lb	850lb	850lb	1210lb	1630lb	850lb	1630lb	850lb	1630lb	3150lb	3150lb	6290lb

Specifications are Subject to Change Without Notice

E & OE